



SIR-30

Rugged, High-Performance Multi-Channel GPR Data Acquisition System

The SIR-30 is the next generation high performance multi-channel radar control unit. This system can collect up to eight channels of data simultaneously with uncompromised performance.

The SIR-30 offers advanced filters and display capabilities for real-time processing including migration, surface positioning, signal floor tracking and adaptive background removal.

As the basis of a high-speed data collection system, the SIR-30 is ideal for: measuring pavement layer thickness, detection of cavities, airport runway assessment, detection of fouled/clean ballast and utility detection.

Typical Uses

- Road structure assessment
- Utility designation
- Bridge deck inspection
- Rail bed inspection



Flexible, Modular Design

- Available in a two, four or eight channel configuration
- Operate the control unit with a laptop computer or as a standalone system
- Compatible with all GSSI antennas

Integrated System

- Ideal for vehicle-mounted applications, supports AC or DC operation
- Full internal GPS logging capability
- Multiple mounting configurations

Deliver Results

- High speed GPR data collection—capable of more than 5,792 scans/second, with four channels
- USB, Ethernet and Compact flash ports for system flexibility
- Up to 500 GB data storage



System

Antenna Support	Compatible with all GSSI antennas
Number of Channels	Records data from 1 to 4 hardware channels simultaneously; two 4 channel systems can be connected to form an 8 channel system
Data Storage	Internal memory: 4 channel 500 GB Internal SSD 2 channel 250 GB Internal SSD GPS data logged internally
Display Modes	Linescan and O-scope. In Linescan display, 256 color bins are used to represent the amplitude and polarity of the signal
Operational Modes	External laptop, standalone with external monitor and keyboard or remote command set

Data Acquisition

Data Format	RADAN (.dzt)																																				
Scan Rate Examples	Output Data Resolution: 32-bit <table border="1"><thead><tr><th colspan="2">1-4 Channels @ 100 KHz PRF</th><th colspan="2">1-4 Channels @ 800 KHz PRF</th></tr><tr><th>Samples</th><th>Max Rate (scans/Sec)</th><th>Samples</th><th>Max Rate (scans/Sec)</th></tr></thead><tbody><tr><td>256</td><td>326</td><td>256</td><td>1449</td></tr><tr><td>512</td><td>178</td><td>512</td><td>990</td></tr><tr><td>1024</td><td>93</td><td>1024</td><td>606</td></tr><tr><td>2048</td><td>48</td><td>2048</td><td>341</td></tr><tr><td>4096</td><td>24</td><td>4096</td><td>182</td></tr><tr><td>8192</td><td>12</td><td>8192</td><td>94</td></tr><tr><td>16,384</td><td>8</td><td>16,384</td><td>48</td></tr></tbody></table>	1-4 Channels @ 100 KHz PRF		1-4 Channels @ 800 KHz PRF		Samples	Max Rate (scans/Sec)	Samples	Max Rate (scans/Sec)	256	326	256	1449	512	178	512	990	1024	93	1024	606	2048	48	2048	341	4096	24	4096	182	8192	12	8192	94	16,384	8	16,384	48
1-4 Channels @ 100 KHz PRF		1-4 Channels @ 800 KHz PRF																																			
Samples	Max Rate (scans/Sec)	Samples	Max Rate (scans/Sec)																																		
256	326	256	1449																																		
512	178	512	990																																		
1024	93	1024	606																																		
2048	48	2048	341																																		
4096	24	4096	182																																		
8192	12	8192	94																																		
16,384	8	16,384	48																																		
Scan Rate Interval	User-selectable																																				
Samples per Scan	256, 512, 1024, 2048, 4096, 8192, 16,384																																				
Operating Modes	Continuous (time) or survey wheel (distance triggered)																																				
Time Range	0-20,000 nanoseconds full scale, user-selectable Gain: manual adjustment from -42 to +126 dB. Number of segments in gain curve is user-selectable from 1 to 8.																																				
Standard Real-Time Filters	Infinite Impulse Response (IIR) - Low and High Pass, vertical and horizontal Finite Impulse Response (FIR) - Low and High Pass, vertical and horizontal																																				
Advanced Real-Time Filters	Migration, Surface Position Tracking, Signal Floor Tracking, Adaptive Background Removal																																				
External Marker	Three different inputs/codes: Antenna, Back panel, Accessory connector																																				
Automatic System Setups	Storage of an unlimited number of system setup files for different survey conditions and/or antenna deployment configurations																																				
Automatic Antenna Recognition	Automatic recognition of Smart Antennas to allow maximum compliant transmit rate																																				

Languages

English

Operating

Operating Temperature	-10°C to 50°C external (14°F to 122°F)
Power	260W max (120W typical) at 95-250VAC 50/60Hz or +10VDC to +28VDC
Transmit Rate	Up to 800 KHz (International), US/Canada and CE rates depend on antenna model

Input/Output

Available Ports	Antenna inputs (2 or 4), Survey wheel, Marker, DC power input, Serial RS232 (GPS port), Sync connector, Accessory connector, HDMI video, Ethernet to PC, 4 USB ports
-----------------	--

Dimensions: 17.7x13x5.1 in (45x33x13cm)
Weight: 18.5 lbs (8.4 kg)
Relative Humidity: <95% non-condensing
Storage Temperature: -40°C to 60°C

Antennas and accessories sold separately.
FCC, RSS-220 and CE Compliant.



www.geophysical.com • sales@geophysical.com

12 Industrial Way • Salem, NH 03079-2837
Tel: (603) 893-1109 • Fax: (603) 889-3984

